



FACTOR - 60 kg

12mm плоскост + 4mm стъкло и 18mm плоскост
mm board and 18mm board


ISO 9001:2000



изчисляване размерите на плоскостите $\neq 12\text{mm} + \text{огледало} \neq 4\text{mm} + 18\text{mm}$ плоскост
BOARD DIMENSIONS $\neq 12\text{mm} + \text{MIRROR} \neq 4\text{mm} + 18\text{mm}$ BOARD

ПЛОСКОСТ $\neq 18$

бродячий наездник	n=2	n=3	n=4	n=5
hp	hp = H - 16mm			
b _p	$b_{p1} = \frac{S+40}{2}$	$b_{p2} = \frac{S+80}{3}$	$b_{p3} = \frac{S+120}{4}$	$b_{p4} = \frac{S+160}{5}$



светлия просвет във височина [mm]

H - opening assembly height [mm]

светлия просвет във ширина [mm]

S - opening assembly width [mm]

височина на плоскостта [mm]

board height [mm]


bp- board width [mm]
ширина на плоскостта [mm]

board width [mm]
височина на огледалото [mm]

hL- височина на огледалото [mm]

ширина на огпелатото [mm]

b_L - ширина на огледалото [mm]



ПЛОСКОСТЬ №12

ОГЛЕДАЛО №4

физическая величина	n=2	n=3	n=4	n=5
$\hbar p$	$\hbar p = \hbar \cdot 19 \text{ nm}^{-1}$			
b_p	$b_p = \frac{S+36}{2}$	$b_p = \frac{S+74}{3}$	$b_p = \frac{S+112}{4}$	$b_p = \frac{S+150}{5}$
$\hbar_L$	$\hbar_L = \hbar p \cdot 4 \text{ nm}$			
b_L	$b_L = \frac{S+28}{2}$	$b_L = \frac{S+62}{3}$	$b_L = \frac{S+96}{4}$	$b_L = \frac{S+130}{5}$

